

The Indigo MGEb system is independently tested and certified to PSA MOB PF2 PS/SPU March 1992

Typical Applications

Communication Rooms
IT Suites

Indigo MGEb

- ✓ Finished in Polyflor SD Steel Grey*
- ✓ ESD floor to PSA MOB
- ✓ Excellent Dimensional Stability
- ✓ Superior Adhesive Technology
 - will not delaminate
- ✓ Highest Density Chipboard Available

* Wide range of finishes available



FACTORY GUARANTEE; PANEL 25YRS PEDESTAL 50YRS



TECHNICAL SPECIFICATION	LOAD CHARACTERISTICS	DIMENSIONS	COMPONENT DETAIL
PSA MOB PF2 PS/SPU	WORKING POINT LOAD 3.0kN ULTIMATE POINT LOAD 9.0kN	MODULE SIZE 600x600mm	Panel: 38mm high-density chipboard core Zinc whisker-free steel bottom.
MEDIUM GRADE	WORKING UDL 12.0KN/M ² ULTIMATE UDL 36.0KN/M ²	THICKNESS 38.8mm (PLUS FINISH)	Pedestal: Heavy gauge steel construction. ABS Conductive Cap
FINISH - Vinyl, HPL, Rubber	SAFETY FACTOR 3	WEIGHT 13.6Kg (WITH VINYL FINISH)	Pedestal available in zinc whisker-free nickel plating
Electrostatic Properties	Surface floor resistance to building earth 5 X 10 ⁹ and 2 X 10 ¹⁰ ohms RH 50% ±10% (PSA MOB T43 test method)		

ACCESS FLOORS DISTRIBUTION LIMITED

PO Box 650
HUNTINGDON, Cambs
PE29 9HF
T/01480 367096
F/01480 330 004

E/sales@accessfloorsdistribution.co.uk
W/www.accessfloorsdistribution.co.uk